



Quick Coat™

SP501, 503-505, 507-510, 512, 513, 515, 525

Product Description

VHT® Quick Coat™ is a premium quality coating, which provides extra hide and durability for interior or exterior applications. This tough and durable coating prevents rust and corrosion on properly prepared surfaces, is fast drying, lead free and ozone safe. It provides a rich weather resistant gloss finish.

Product Characteristics

Color: Fire Red, Bright Orange, Gloss Black, Ocean Blue, Bright Aluminum, Bright Yellow, Gloss White, Flat Black, Forest Green, Machinery Gray, Clear, and Silver Chrome

Finish: Flat, Satin, and Gloss

Properties

Product Weight: 6.04 lb/gal

Flash Point: Propellant < 0° F

Coating System

VHT provides a multi-high performance coating system for the ultimate in protection and quality. This system includes surface preparation , prime, paint, and clear coat.

Prep SP445 Prep Spray

Prime SPxxx Prime Coat Color

Coat SPxxx Quick Coat Color

Clear SPxxx Quick Coat Clear

Uses

Tools, Wood, and Household Projects

Surfaces:

- Wood, Metal, and Sealed Plaster & Masonry Surfaces

Application

Prepare surface by removing loose paint, dirt, rust, grease, wax, etc. Use grease and wax remover to clean surface. Lightly sand-surface with 320-grit sandpaper, wet or dry. Wipe surface down again with grease or wax remover.

Mask-off surrounding areas to protect from overspray. Use at temperatures between 60° F (16° C) and 95° F (35° C) and when humidity is less than 60%.

Shake can vigorously for one full minute after mixing ball moves freely. Shake can for 10 seconds after each minute of use. If bare metal is exposed, apply VHT prime coat primer first. To spray, hold can parallel 8-10 inches from the surface to be painted and use in an even, sweeping motion. Apply 2 light coats, followed by 1 medium wet coat. Apply all coats within 1 hour, allowing 10 minutes between each coat. For additional coats after 1 hour, wait 7 days for paint to cure. Dries to the touch in 20 minutes and can be handled in 3 hours. Covers approximately 12-14 square feet.

No curing required

Packaging

Fill Weight: 11.25 oz

Per Case: 6 cans

Case Weight: 5.82 lbs

Cases/Pallet: 156

Units/Pallet: 936 cans